

## INDEX G200 YB

**Kind :** CNC lathe  
**Brand :** INDEX  
**Model :** G200 YB  
**Year :** 2001  
**Serial Nr:** 511284  
**Stock Nr :** 10257



### TECHNICAL DETAILS

- Number of axes : 9
- Number of spindles : 2
- Number of turrets : 2
- MAIN SPINDLE
- Spindle nose : A2-5"
- Spindle power : 20/29 [kW]
- Spindle speeds : 5.000 [rpm]
- Max. bar diameter : 65 [mm]
- Max. turning diameter : 200 [mm]
- C axis indexing precision : 0,001 [°]
- COUNTER-SPINDLE
- Spindle nose : A2-5"
- Spindle power : 13/22 [kW]
- Spindle speeds : 5.000 [rpm]
- Max. bar diameter : 60 [mm]
- C axis indexing precision : 0,001 [°]
- Travel : 445 [mm]
- TURRET
- Number of positions : 14
- Number of motorized positions : 14
- X/Z stroke : 155/590 [mm]
- Y stroke : 120 [mm]
- B Axis stroke : 360 [°]
- Tool holder type : VDI 25

**Kind : CNC lathe**  
**Brand : INDEX**  
**Model : G200 YB**  
**Year : 2001**  
**Serial Nr: 511284**  
**Stock Nr : 10257**

- Live tools speed : 6.000 [rpm]  
MILLING SPINDLE  
- Spindle speeds : 6.000 [rpm]  
- Spindle power : 5,5 [kW]  
LOWER LEFT TURRET  
- Number of positions : 14  
- Number of motorized positions : 14  
- X/Z stroke : 105/400 [mm]  
- Tool holder type : VDI 25  
- Live tools speed : 6.000 [rpm]  
POWER SUPPLY  
- Supply voltage : 400 [V]  
- Total installed power : 39 [kW]  
WEIGHT & DIMENSIONS  
- Machine floor space : 3.450 x 2.520 [mm]  
- Machine height : 2.650 [mm]  
- Machine weight : 4.800 [kg]

#### **EQUIPMENT**

- CNC : INDEX C200-4 (Siemens 840C)  
- Tailstock option with counterspindle : Ethernet / RS232 / USB / PCMCIA  
- Coolant tank : KNOLL  
- Chips conveyor : Right  
- Tool probe : Renishaw  
- Tool breakage detection  
- Parts catcher  
- Chuck 3 jaws : SMW 210BH  
- Collet chuck : HAINBUCH Spanntop 65  
- Number of fixed tool holders : 28  
- Number of turning tool holders : 6